

## DH-PFS3206-4P-96

### 4-Port PoE Switch (Unmanaged)



### Features

- > Two-layer unmanaged PoE switch
- > Cascade can be realized via SFP fiber port
- > MAC auto study and aging, MAC address list capacity is 8K
- > Support IEEE802.3af, IEEE802.3at, Hi-PoE standard
- > Conform IEEE802.3, IEEE802.3u, IEEE802.3ab/z and IEEE802.3X standards
- > Industrial wide temperature design

## DH-PFS3206-4P-96

### Technical Specifications

Model	DH-PFS3206-4P-96
Ethernet Port	2*1000 Base-X、 1*10/100/1000 Base-T (Hi-PoE/PoE+/PoE)、 3*10/100 Base-T (PoE+/PoE)
PoE Power Consumption	Port1、2、3 ≤30W, Port4≤60W Total≤96W
PoE Protocol	IEEE802.3af、 IEEE802.3at、 Hi-PoE
Switching Capacity	6.8G
Packet Forwarding Rate	4.91Mpps
Packet Buffer Memory	1Mb
MAC Table Size	8K
Flow Control	Enable by default
Application Humidity	10%—90%
Power	DC: 48~57V
Lightning Protection	Common Mode 4KV Differential Mode 2KV
Working Temperature	- 30℃~65℃
Weight	480g
Dimension(W×D×H)	150mm×100mm×30mm

### Accessories

Model	
PFT3950	1.25G 850nm,500m,LC, Multi-mode
PFT3960	1.25G 1310/1550nm,20km,LC, Single-mode
PFT3970	1.25G 1550/1310nm,20km,LC, Single-mode

#### Dahua Technology Co., Ltd.

1187 BinAn Road, Binjiang District, Hangzhou, China

Tel: +86-571-87688883

Fax: +86-571-87688815

Email:overseas@dahuatech.com

www.dahuatech.com

\*Design and specifications are subject to change without notice.

© 2012 Dahua Technology Co., Ltd.