

12V PSU for Hub/Hub Plus/ReX

A power supply unit, connecting Hub/Hub Plus control panels and ReX radio signal range extender to low-voltage power sources.

DC input	Input voltage 8-20 V
----------	----------------------

Use Ajax in premises lacking electricity or having an unstable power supply. A 12 V power supply unit allows connecting hubs and radio signal extenders to low-voltage networks or use an external battery.

Ajax protects your home, even if it goes on wheels. With a 12 V power supply, the security system can travel with you, connecting to a car or portable battery.

Compatibility

The power supply unit is compatible with Hub, Hub Plus, and ReX. It features a standard socket for connecting the power jack plug and has a bundled terminal adapter.

Installation

12V PSU is installed into the device body, replacing the pre-installed 110/230 V power supply unit.

Tech Specs

Compatibility	<u>Hub</u> , <u>Hub Plus</u> , <u>ReX</u>
Input voltage	8-20 V DC
Output voltage	4.65 V \pm 3%
Switch-on voltage	8 V \pm 2.5%
Switch-off voltage	6.9-7.5 V (depending on load)

Input current	<1 A
Output current	1,5 A
Connection	Socket: 6,5 x 2 mm Plug: 5,5 x 2,1 mm (power jack)
Dimensions	138 x 64 x 13 mm
Weight	30 g
Complete set	<ol style="list-style-type: none">1. 12V PSU for Hub/Hub Plus/ReX2. Terminal adapter3. Quick guide